



中国认可
国际互认
检测
TESTING
CNAS L0916

TYPE-EXAMINATION CERTIFICATE OF SPECIAL EQUIPMENT (LIFT)

No. TSX F33003820170007

A

Name of Applicant: GUANGDONG HUAHUI ELEVATOR ACCESSORIES CO.,LTD.
Registered Address of Applicant: West of Gangkou Road,Dongqu Sanshan,Guicheng Street,Nanhai District,Foshan City,Guangdong Province
Name of Manufacturer: GUANGDONG HUAHUI ELEVATOR ACCESSORIES CO.,LTD.
Manufacturing Address: West of Gangkou Road,Dongqu Sanshan,Guicheng Street,Nanhai District,Foshan City,Guangdong Province
Product Category: Lift Safety Protection Device
Product Name: Hydraulic buffer Model/Type: HYF160
Type-Examination Report No. 2017AF0052

With the Type-Examination, it is confirmed that the product is compliance with the regulations of *Regulation for Type Test of Lifts (TSG T7007-2016)*.

The product is in compliance with related regulations of *GB 7588-2003 Safety Rules for the Construction and Installation of Electric Lifts(Including No.1 amending list)* and *EN81-1+A3 :2009 Safety rules for the construction and installation of lifts-part 1: Electric lifts*

The certificate covers the following different size products of the same type mentioned below:

HYF160

Please refer to the annex for the specific parameters and configuration.

(Stamp)

Issued Date: **2017-1-10**

Date for Recertification: /-/ /

Next Verification Before: **2019-1-9**

SHENZHEN INSTITUTE OF SPECIAL EQUIPMENT INSPECTION AND TEST

GUANGDONG STATION OF ELEVATOR QUALITY SUPERVISION AND TEST (SHENZHEN)

Notes: 1. The applicant has the responsibility to ensure the products being in compliance with standard and also ensure the consistence of product and type tested sample.

2. The certificate cannot apply to products produced after next verification date.



中国认可
国际互认
检测
TESTING
CNAS L0916

TYPE-EXAMINATION CERTIFICATE ANNEXED TABLE (LIFT)

| | | | |
|-------------------|---------------------|-----------------------------|---------------|
| Certificate No. | TSX F33003820170007 | | |
| Equipment Type | Buffer | | |
| Product Name | Hydraulic buffer | Model/Type | HYF160 |
| Rated Speed | ≤1.5m/s | Maximum Impacted Speed | 1.725m/s |
| Minimum Mass | 500kg | Maximum Mass | 3000kg |
| Maximum Stroke | 160mm | Buffer Liquid Specification | HF-2 68/0.56L |
| Throttle Type | Annular overflow | Reset Mode | Spring return |
| Working Condition | Indoor | | |

