









中国认可 国际互认 检测 TESTING CNAS L0916

## TYPE-EXAMINATION CERTIFICATE OF SPECIAL EQUIPMENT (LIFT)

No. TSX F33003820170007

Name of Applicant: GUANGDOUNG HUAHUI ELEVATOR ACCESSORIES CO.,LTD.

Registered Address of WestofGangkouRoad,DongguSanshan,GuichengStreet,Nanhai

Applicant: District, Foshan City, Guangdong Province

Name of Manufacturer: GUANGDOUNG HUAHUI ELEVATOR ACCESSORIES CO.,LTD.

Manufacturing Address: WestofGangkouRoad,DongquSanshan,GuichengStreet,Nanhai

District, Foshan City, Guangdong Province

Product Category: Lift Safety Protection Device

Product Name: Hydraulic buffer Model/Type: HYF160

Type-Examination Report No. 2017AF0052 This verification Report No. 2018AF1215

With the Type-Examination, it is confirmed that the product is compliance with the regulations of *Regulation for Type Test of Lifts (TSG T7007-2016)*.

The product is in compliance with related regulations of *GB 7588-2003 Safety Rules for the Construction* and Installation of Electric Lifts(Including No.1 amending list) and EN81-1+A3:2009 Safety rules for the construction and installation of lifts-part 1: Electric lifts

The certificate covers the following different size products of the same type mentioned below: HYF160

Please refer to the annex for the specific parameters and configuration.

(Stamp)

Issued Date: 10-Jan-2018

Date for Recertification: 1 -Nov-2018

Next Verification Before: 8 - Jan- 2021

## SHENZHEN INSTITUTE OF SPECIAL EQUIPMENT INSPECTION AND TEST GUANGDONG STATION OF ELEVATOR QUALITY SUPERUISION AND TEST (SHENZHEN)

Notes: 1. The applicant has the responsibility to ensure the products being in compliance with standard and also ensure the consistence of product and type tested sample.

2. The certificate cannot apply to products produced after next verification date.









中国认可 国际互认 检测 TESTING CNAS L0916

## TYPE-EXAMINATION CERTIFICATE ANNEXED TABLE (LIFT)

Certificate No.	TSX F33003820170007		
Equipment Type	Lift Safety Production Device		
Product Name	Hydraulic buffer	Model/Type	HYF160
Rated Speed	≤1.5m/s	Maximum Impacted Speed	1.73m/s
Minimum Mass	500kg	Maximum Mass	3000kg
Maximum Stroke	160mm	Buffer Liquid Specification	HF-2 68#Anti-wear hydraulic oil / 0.56 L
Throttle Type	Ring gap throttle	Reset Mode	External upper spring reset
Working Condition	Indoor		
Other Staements	Documents identification number: XPSQ2018090113AENZS		